






Easyfix K-DAG Steel Post (90x90mm) has been designed to perform maximum strenght with mimimum material to keep it economically. The panels are fixed to post without accessories such as screws, bolts, clips or clamps. As a result it avoids damage on materials during fastening. Slots are at every 100mm and each post is covered with a plastic cap.





Flexible Production





SPECIFICATIONS

| Coating | NANO coating on Galvanised steel wire to ensure high adhesion and as final layer either electrostatic polyester powder coating (min.80 μm) or thermoplastic coating (min.150 μm) | | | | | |
|-----------------|--|--|--|--|--|--|
| Post Section | 90 x 90 mm | | | | | |
| Fixation | Slots at 100 mm intervals | | | | | |
| Thickness Range | 0,90 - 1,35 mm | | | | | |
| I/V | 8,67 cm³ (according to 1.20 mm) | | | | | |

⁹⁰ mm



NANO COATING

NANO coating is a special technology that increases the adhesion performance of the coating to the metal surface and creates pores in NANO sizes. Thanks to these pores, the powder coating adheres with high performance on metal surface.



^{* %5} overall tolerance





| Post Lengths | | | | | | | | | | | | | |
|---------------------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|
| Panel heights | 630 mm | 830 mm | 1030 mm | 1230 mm | 1430 mm | 1530 mm | 1630 mm | 1730 mm | 1830 mm | 1930 mm | 2030 mm | 2230 mm | 2430 mm |
| Post length at concrete surface | 670 mm | 870 mm | 1070 mm | 1270 mm | 1470 mm | 1570 mm | 1670 mm | 1770 mm | 1870 mm | 1970 mm | 2070 mm | 2270 mm | 2470 mm |
| Post length at soil surface | 1070 mm | 1270 mm | 1470 mm | 1670 mm | 1970 mm | 2070 mm | 2170 mm | 2270 mm | 2370 mm | 2470 mm | 2570 mm | 2770 mm | 2970 mm |


^{*} The given dimensions are advisable. Based on project requirement different dimensions could be used. %5 overall tolerance.

Fence Post Fixation Details

Fixation by tensioning








Solar Cap

Kösedağ is the first company in the world which designed K-Dag solar cap for a fence post. Easy fixation because of no wiring. Made out of polycarbon to show antivandal features. Maximum illumination with minimum energy consumption. IP65 protection class certificated.





Installation Types





Suitable Panels







K-DAG plastic cap Custom designed, easy fixed, aesthetic plastic cap.

Accessories

K-DAG Removable Base Plate


Removable base plate is designed for Easyfix K-DAG steel post and is a smart solution to save stock cost.





APPLICATION AREAS























Estates

Airports











Road & Transport

Public Buildingd









